



Taśma GERLED® Professional NANO SMD 5050 12V

GERLED® Professional LED strip
NANO SMD 5050 12V

GERLED® Professional striscia LED
NANO SMD 5050 12V

GERLED® Professional LED-Streifen
NANO SMD 5050 12V



Podwójna warstwa PCB
Double PCB laminate
PCB a doppio strato
Doppelte PCB-Schicht



Stopień ochrony NANO
Protection class
Grado di protezione (IP)
IP-Klasse



3 lata gwarancji
3 years warranty
3 anni di garanzia
3 Jahre Garantie




Współczynnik oddawania barw
Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE
CE Compliance
Conformità CE
CE-Zertifikat




Żywotność
Life span
Vitalità
Lebensdauer



Kąt świecenia
Viewing angle
Angolo luminoso
Beleuchtungswinkel



Temperatura pracy
Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura magazynowania
Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS
RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

| KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE | BARWA LIGHT COLOR COLORE FARBE | TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR | ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS | POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG | STRUMIEN ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM |
|--|---|---|---|--|--|
| TGN0053BC | BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS | 2900K-3100K | 60 LED/m | 14,4 W/m | 1070 lm/m |
| TGN0053BN | BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS | 3900K-4300K | 60 LED/m | 14,4 W/m | 1241 lm/m |
| TGN0053BZ | BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS | 6000K-6500K | 60 LED/m | 14,4 W/m | 1256 lm/m |

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)

