



Taśma GERLED® Professional IP20 SMD 2835 12V S-TYPE

GERLED® Professional LED strip IP20 SMD 2835 12V S-TYPE GERLED® Professional striscia LED IP20 SMD 2835 12V S-TYPE GERLED® Professional LED-Streifen IP20 SMD 2835 12V S-TYPE



Podwójna warstwa PCB
Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



IP20
Stoień ochrony IP20
Protection class
Grado di protezione (IP)
IP-Klasse



3 lata
3 lata gwarancji
3 years warranty
3 anni di garanzia
3 Jahre Garantie



CRI >85
Współczynnik oddawania barw
Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE
CE Compliance
Conformità CE
CE-Zertifikat




min. 50 000 h
Żywotność
Life span
Vitalità
Lebensdauer



180°
Kąt świecenia
Viewing angle
Angolo luminoso
Beleuchtungswinkel



-25°C ÷ +60°C
Temperatura pracy
Operational temperature
Temperatura d'esercizio
Arbeitstemperatur




-40°C ÷ +80°C
Temperatura magazynowania
Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS
RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GWW3028BC008	BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	4,8 W/m	468 lm/m
05TS12GWW3028BN008	BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	4,8 W/m	475 lm/m
05TS12GWW3028BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	4,8 W/m	450 lm/m

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)



2 mm
wysokość
height
altezza
Höhe

6 mm
szerokość / width / larghezza / Breite