



Taśma GERLED® Professional IP20 SMD 2835 12V S-TYPE

GERLED® Professional LED strip
INTERNAL SMD 2835 12V S-TYPE

GERLED® Professional striscia LED
DA INTERNO SMD 2835 12V S-TYPE

GERLED® Professional LED-Streifen
INNERER SMD 2835 12V S-TYPE



Podwójna warstwa PCB
Double PCB laminate
PCB a doppio strato
Doppelte PCB-Schicht



Stożek ochrony IP20
Protection class
Grado di protezione (IP)
IP-Klasse



3 lata gwarancji
3 years warranty
3 anni di garanzia
3 Jahre Garantie




Współczynnik oddawania barw
Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE
CE Compliance
Conformità CE
CE-Zertifikat



Żywotność
Life span
Vitalità
Lebensdauer



Kąt świecenia
Viewing angle
Angolo luminoso
Beleuchtungswinkel



Temperatura pracy
Operational temperature
Temperatura d'esercizio
Arbeitstemperatur




Temperatura magazynowania
Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS
RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKT CODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDES	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
TGWVG28BC	BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	9,6 W/m	500 lm/m
TGWVG28BN	BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	9,6 W/m	620 lm/m
TGWVG28BZ	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	9,6 W/m	620 lm/m

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)