



Taśma GERLED® Professional IP20 SMD 2835 12V 5mm

GERLED® Professional LED strip
IP20 SMD 2835 12V 5mm

GERLED® Professional striscia LED
IP20 SMD 2835 12V 5mm

GERLED® Professional LED-Streifen
IP20 SMD 2835 12V 5mm



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



IP20

Stopień ochrony IP20

Protection class
Grado di protezione (IP)
IP-Klasse



3 lata

3 lata gwarancji

3 years warranty
3 anni di garanzia
3 Jahre Garantie



CRI >85

Współczynnik oddawania barw

Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



min.
50 000 h

Żywotność

Life span
Vitalità
Lebensdauer



180°

Kąt świecenia

Viewing angle
Angolo luminoso
Beleuchtungswinkel



-25°C+60°C

Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



-40°C+80°C

Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKT CODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEN ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GW53028BC008	BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	4,8 W/m	468 lm/m
05TS12GW56028BC008			120 LED/m	9,6 W/m	905 lm/m
05TS12GW53028BN008	BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	4,8 W/m	468 lm/m
05TS12GW56028BN008			120 LED/m	9,6 W/m	930 lm/m
05TS12GW53028BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	4,8 W/m	450 lm/m
05TS12GW56028BZ008			120 LED/m	9,6 W/m	900 lm/m
05TS12GW5302812K08	BIAŁY ZIMNY 12500K COOL WHITE 12500K BIANCO FREDDO 12500K KALTWEISS 12500K	10000K-13000K	60 LED/m	4,8 W/m	492 lm/m
05TS12GW5602812K08			120 LED/m	9,6 W/m	985 lm/m

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)




2 mm
wysokość
height
altezza
Höhe

5 mm
szerokość / width / larghezza / Breite

120 LED/m



sekcja cięcia co 25 mm (3 diody)
cut section every 25 mm (3 diodes)
sezione di taglio ogni 25 mm (3 diodi)
Schnittabschnitt alle 25 mm (3 LEDs)



2 mm
wysokość
height
altezza
Höhe

5 mm
szerokość / width / larghezza / Breite