



Taśma GERLED® Professional NANO SMD 5050 12V

GERLED® Professional LED strip NANO SMD 5050 12V

GERLED® Professional striscia LED NANO SMD 5050 12V

GERLED® Professional LED-Streifen NANO SMD 5050 12V



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony NANO

Protection class
Grado di protezione (IP)
IP-Klassee



3 lata

3 lata gwarancji
3 years warranty
3 anni di garanzia
3 Jahre Garantie



CRI >85

Współczynnik oddawania barw
Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex




Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



Zywotność

Life span
Vitalità
Lebensdauer



Kąt świecenia

Viewing angle
Anglo luminoso
Beleuchtungswinkel



Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat


KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GN01550BC008	BIAŁY CIEPLY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	30 LED/m	7,2 W/m	550 lm/m
05TS12GN03050BC008			60 LED/m	14,4 W/m	1070 lm/m
05TS12GN01550BN008	BIAŁY NUETRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	30 LED/m	7,2 W/m	605 lm/m
05TS12GN03050BN008			60 LED/m	14,4 W/m	1241 lm/m
05TS12GN01550BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	30 LED/m	7,2 W/m	614 lm/m
05TS12GN03050BZ008			60 LED/m	14,4 W/m	1256 lm/m

30 LED/m




sekcja cięcia co 100 mm (3 diody)
cutsection every 100 mm (3 diodes)
sezione di taglio ogni 100 mm (3 diodi)
Schnittabschnitt alle 100 mm (3 LEDs)

2 mm
wysokość
height
altezza
Höhe




10 mm
szerokość / width / larghezza / Breite

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cutsection every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)

2 mm
wysokość
height
altezza
Höhe



10 mm
szerokość / width / larghezza / Breite