



# Taśma GERLED® Professional NANO SMD 5050 12V

GERLED® Professional LED strip  
NANO SMD 5050 12V

GERLED® Professional striscia LED  
NANO SMD 5050 12V

GERLED® Professional LED-Streifen  
NANO SMD 5050 12V



Podwójna warstwa PCB

Double PCB laminate  
PCB a doppio laminate  
Doppelte PCB-Schicht



Stopień ochrony NANO

Protection class  
Grado di protezione (IP)  
IP-Klassee



3 lata gwarancji

3 years warranty  
3 anni di garanzia  
3 Jahre Garantie



Współczynnik oddawania barw

Color rendering index  
Indice di resa cromatica (Ra)  
Farbwiedergabeindex




Zgodność z CE

CE Compliance  
Conformità CE  
CE-Zertifikat



Żywotność

Life span  
Vitalità  
Lebensdauer



Kąt świecenia

Viewing angle  
Anglo luminoso  
Beleuchtungswinkel



Temperatura pracy

Operational temperature  
Temperatura d'esercizio  
Arbeitstemperatur



Temperatura magazynowania

Storage temperature  
Temperatura di stoccaggio  
Lagertemperatur



Zgodność z RoHS

RoHS Compliance  
Conformità RoHS  
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GN01550RGBXX	RGB	R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS12GN03050RGBXX			60 LED/m	14,4 W/m	
05TS12GN01550RGC08	RGB + BIAŁY CIEPŁY RGB + WARM WHITE RGB + BIANCO CALDO RGB + WARMWEISS	2900K-3100K R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS12GN03050RGC08			60 LED/m	14,4 W/m	
05TS12GN01550RGZ08	RGB + BIAŁY ZIMNY RGB + COOL WHITE RGB + BIANCO FREDDO RGB + KALTWEISS	6000K-6500K R:633 G:517 B:450	30 LED/m	7,2 W/m	310-315 lm/m
05TS12GN03050RGZ08			60 LED/m	14,4 W/m	

## 30 LED/m



sekcja cięcia co 100 mm (3 diody)  
cutsection every 100 mm (3 diodes)  
sezione di taglio ogni 100 mm (3 diodi)  
Schnittabschnitt alle 100 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



10 mm  
szerokość / width / larghezza / Breite

## 60 LED/m



sekcja cięcia co 50 mm (3 diody)  
cutsection every 50 mm (3 diodes)  
sezione di taglio ogni 50 mm (3 diodi)  
Schnittabschnitt alle 50 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



10 mm  
szerokość / width / larghezza / Breite