



Taśma GERLED® Professional NANO SMD 2835 12V 5mm

GERLED® Professional LED strip NANO SMD 2835 12V 5mm GERLED® Professional striscia LED NANO SMD 2835 12V 5mm GERLED® Professional LED-Streifen NANO SMD 2835 12V 5mm



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony NANO

Protection class
Grado di protezione (IP)
IP-Klasse



3 lata

3 lata gwarancji
3 years warranty
3 anni di garanzia
3 Jahre Garantie



CRI >85

Współczynnik oddawania barw
Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



min.
50 000 h

Żywotność

Life span
Vitalità
Lebensdauer



180°

Kąt świecenia

Viewing angle
Angolo luminoso
Beleuchtungswinkel



-25°C +60°C

Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



-40°C +80°C

Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS


RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

| KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKT CODE | BARWA LIGHT COLOR COLORE FARBE | TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR | ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS | POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG | STRUMIEN ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM |
|---|---|---|---|--|--|
| 05TS12GN53028BC008 | BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS | 2900K-3100K | 60 LED/m | 4,8 W/m | 468 lm/m |
| 05TS12GN56028BC008 | | | 120 LED/m | 9,6 W/m | 905 lm/m |
| 05TS12GN53028BN008 | BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS | 3900K-4300K | 60 LED/m | 4,8 W/m | 468 lm/m |
| 05TS12GN56028BN008 | | | 120 LED/m | 9,6 W/m | 930 lm/m |
| 05TS12GN53028BZ008 | BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS | 6000K-6500K | 60 LED/m | 4,8 W/m | 450 lm/m |
| 05TS12GN56028BZ008 | | | 120 LED/m | 9,6 W/m | 900 lm/m |
| 05TS12GN5302812K08 | BIAŁY ZIMNY 12500K COOL WHITE 12500K BIANCO FREDDO 12500K KALTWEISS 12500K | 10000K-13000K | 60 LED/m | 4,8 W/m | 492 lm/m |
| 05TS12GN5602812K08 | | | 120 LED/m | 9,6 W/m | 985 lm/m |

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)




szerokość / width / larghezza / Breite

120 LED/m



sekcja cięcia co 25 mm (3 diody)
cut section every 25 mm (3 diodes)
sezione di taglio ogni 25 mm (3 diodi)
Schnittabschnitt alle 25 mm (3 LEDs)



szerokość / width / larghezza / Breite