



Taśma GERLED® Professional IP20 SMD 5630 24V

GERLED® Professional LED strip
IP20 SMD 5630 24V

GERLED® Professional striscio LED
IP20 SMD 5630 24V

GERLED® Professional LED-Streifen
IP20 SMD 5630 24V



Podwójna warstwa
PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony
IP20

Protection class
Grado di protezione (IP)
IP-Klasse



3 lata gwarancji

3 years warranty
3 anni di garanzia
3 Jahre Garantie



Współczynnik
oddawania barw

Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



Żywotność

Life span
Vitalità
Lebensdauer



Kąt świecenia

Viewing angle
Angolo luminoso
Beleuchtungswinkel



Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura
magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat


KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKT CODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS24GW03056BC008	BIAŁY CIEPŁY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	14,4 W/m	1710 lm/m
05TS24GW03056BN008	BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	14,4 W/m	1762 lm/m
05TS24GW03056BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	14,4 W/m	1850 lm/m

60 LED/m



sekcja cięcia co 100 mm (6 diody)

cut section every 100 mm (6 diodes)
sezione di taglio ogni 100 mm (6 diodi)
Schnittabschnitt alle 100 mm (6 LEDs)



szerość / width / larghezza / Breite