



Taśma GERLED® Professional NANO SMD 2835 12V

GERLED® Professional LED strip
NANO SMD 2835 12V

GERLED® Professional striscia LED
NANO SMD 2835 12V

GERLED® Professional LED-Streifen
NANO SMD 2835 12V



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony NANO

Protection class
Grado di protezione (IP)
IP-Klassee



3 lata gwarancji

3 years warranty
3 anni di garanzia
3 Jahre Garantie




Współczynnik oddawania barw

Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex



Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



Zywotność

Life span
Vitalità
Lebensdauer



Kąt świecenia

Viewing angle
Anglo luminoso
Beleuchtungswinkel



Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GN03028BC008	BIAŁY CIEPLY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	4,8 W/m	468 lm/m
05TS12GN06028BC008			120 LED/m	9,6 W/m	905 lm/m
05TS12GN03028BN008	BIAŁY NUETRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	4,8 W/m	475 lm/m
05TS12GN06028BN008			120 LED/m	9,6 W/m	930 lm/m
05TS12GN03028BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	4,8 W/m	450 lm/m
05TS12GN06028BZ008			120 LED/m	9,6 W/m	900 lm/m
05TS12GN0302812K08	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	10000K-13000K	60 LED/m	4,8 W/m	453 lm/m
05TS12GN0602812K08			120 LED/m	9,6 W/m	906 lm/m

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)

2 mm
wysokość
height
altezza
Höhe



8 mm
szerokość / width / larghezza / Breite

120 LED/m



sekcja cięcia co 25 mm (3 diody)
cut section every 25 mm (3 diodes)
sezione di taglio ogni 25 mm (3 diodi)
Schnittabschnitt alle 25 mm (3 LEDs)

2 mm
wysokość
height
altezza
Höhe



8 mm
szerokość / width / larghezza / Breite