



# Taśma GERLED® Professional NANO SMD 5025 12V BICOLOR

GERLED® Professional LED strip NANO SMD 5025 12V BICOLOR  
 GERLED® Professional striscia LED NANO SMD 5025 12V BICOLOR  
 GERLED® Professional LED-Streifen NANO SMD 5025 12V BICOLOR



Podwójna warstwa PCB

Double PCB laminate  
PCB a doppio laminate  
Doppelte PCB-Schicht



Stopień ochrony NANO

Protection class  
Grado di protezione (IP)  
IP-Klasse



3 lata

3 lata gwarancji

3 years warranty  
3 anni di garanzia  
3 Jahre Garantie



CRI >85

Współczynnik oddawania barw  
Color rendering index  
Indice di resa cromatica (Ra)  
Farbwiedergabeindex



Zgodność z CE


CE Compliance  
Conformità CE  
CE-Zertifikat



min.  
50 000 h

Żywotność

Life span  
Vitalità  
Lebensdauer



180°

Kąt świecenia

Viewing angle  
Anglo luminoso  
Beleuchtungswinkel



-25°C ÷ +60°C

Temperatura pracy

Operational temperature  
Temperatura d'esercizio  
Arbeitstemperatur



-40°C ÷ +80°C

Temperatura magazynowania

Storage temperature  
Temperatura di stoccaggio  
Lagertemperatur



Zgodność z RoHS

RoHS Compliance  
Conformità RoHS  
RoHS-Zertifikat

| KOD PRODUKTU<br>PRODUCT CODE<br>CODICE PRODOTTO<br>PRODUKTCODE | BARWA<br>LIGHT COLOR<br>COLORE<br>FARBE   | TEMPERATURA BARWOWA<br>COLOR TEMPERATURE<br>TEMPERATURA DI COLORE<br>FARBTEMPERATUR | ILOŚĆ DIOD<br>LED QUANTITY<br>NUMERO DIODI<br>ANZAHL DER LEDS | POBÓR MOCY<br>POWER CONSUMPTION<br>POTENZA<br>NENNLEISTUNG | STRUMIEN ŚWIETLNY<br>LUMINOUS FLUX<br>FASCIO LUMINOSO<br>LICHSTROM |
|--|---|---|---|--|--|
| 05TS12GN01552BIC08   | BIAŁY CIEPŁY/NEUTRALNY/ZIMNY<br>WARM/NEUTRAL/COOL WHITE<br>BIANCO CALDO/NATURALE/FREDDO<br>WARMWEISS/NEUTRALWEISS/KALTWEISS | 2900K-6500K   | 30 LED/m  | 7,2 W/m  | 550 lm/m   |
| 05TS12GN03052BIC08   |   |   | 60 LED/m  | 14,4 W/m   | 1020 lm/m  |

30 LED/m



sekcja cięcia co 100 mm ( 3 diody )  
cut section every 100 mm (3 diodes)  
sezione di taglio ogni 100 mm (3 diodi)  
Schnittabschnitt alle 100 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



10 mm  
szerokość / width / larghezza / Breite

60 LED/m



sekcja cięcia co 50 mm ( 3 diody )  
cut section every 50 mm (3 diodes)  
sezione di taglio ogni 50 mm (3 diodi)  
Schnittabschnitt alle 50 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



10 mm  
szerokość / width / larghezza / Breite